

New series 5

Series 5 is a great partner not only for small farms, but also for businesses where everyday **smaller tasks** need to be handled.

The tractor combines **high-quality components, robust mechanical design and simple operation**. Thanks to its versatility, it is a reliable partner in the field, on the farm, in livestock operations and in municipal applications. It easily handles feed mixers, transport, site maintenance and everyday tasks. Customers can choose between a **basic mechanical version** for easy maintenance and maximum simplicity, or a more **comfortable version with PowerShuttle and PowerShift** transmission for greater comfort, efficiency and smoother operation.

A reliable partner for everyday tasks...

Technical specifications

New series 5		5100	5115	5125
ENGINE				
Type	-	FPT F28TCA STAGE V	FPT F36 STAGE V	
Max. Engine Power ISO14396	kW	75	83	90
	HP	102	113	122
Rated Speed	rpm	2300	2200	2300
Max. Engine Torque	Nm	415	460	490
	rpm	1500	1400	1400
Fuel Tank	l	120	130	
Ad Blue Tank	l	16		
TRANSMISSION				
Number of Gears (F/R)	-	24x24		
Reverser	-	SynchroShuttle	PowerShuttle	
PowerShift	-	-	2-speed PowerShift	
Max. Speed	km/h	40[1]		
PTO				
Type	-	Independent Dual Speed		
Rear PTO speeds	rpm	540/1000 (540/540E OPT)		
Front PTO speeds (OPT)	rpm	1000		
HYDRAULICS				
Type	-	Mechanical with regulation		
Gear pump capacity	l/min	65	80	
Rear hydraulic remotes	-	4		
Working pressure	bar	190		
THREE-POINT HITCH				
Type	-	Electrohydraulic		
Category	-	Cat. II		
Max. lift capacity	kg	4500	5500	
Fender TPH control	-	Standard		
Front TPH	-	OPT		
UNDERCARRIAGE				
Drive system		4WD		
Differantial Lock	-	Electro Hydraulic		
Trailer brakes	-	Pneumatic 2+1 hoses		
Quick coupling for air hose	- -	Standard		
OTHER SPECIFICATIONS				
Max operating Weight	kg	4250	4800	
Max Length with front weights Total	mm	4291	4531	
Width	mm	2040[2]		
Total Height	mm	2751-2821	2847-2917	
Wheelbase	mm	2391	2507	

[1] depending on selected tyres, value is approximate

[2] depending on selected tyres